


**A laminate useful as a membrane-electrode assembly for fuel cells,  
production process therefor and a fuel cell provided with the laminate**

**Patent number:** EP1496561  
**Publication date:** 2005-01-12  
**Inventor:** FUKUTA KENJI (JP); SADASUE KAZUYUKI (JP);  
ISOMURA TAKENORI (JP); SAKATA KANJI (JP)  
**Applicant:** TOKUYAMA CORP (JP)  
**Classification:**  
- international: H01M8/10  
- european:  
**Application number:** EP20040254135 20040709  
**Priority number(s):** JP20030195499 20030711; JP20030204483 20030731

Also published as:

 US2005042489 (A1)

Report a data error here

**Abstract of EP1496561**

A laminate consisting of an ion exchange membrane layer comprising a porous film reinforcement and a crosslinked ion exchange resin and a conductive layer formed on at least one side of the ion exchange membrane layer and comprising conductive inorganic particles and a crosslinked ion exchange resin, wherein the ion exchange membrane layer and the conductive layer are integrated with each other by the above ion exchange resins constituting these layers. <??>This laminate is excellent in dimensional stability, heat resistance and methanol impermeability, which makes it suitable for use in electrochemical devices such as a direct methanol type fuel cell as a membrane-electrode assembly, has high bonding properties between the electrode layer and the ion exchange membrane layer of the membrane-electrode assembly, and provides a fuel cell whose output is not reduced by long-term use.

---

Data supplied from the **esp@cenet** database - Worldwide